

EXHIBIT A

(12) **United States Patent**
Snyder

(10) **Patent No.:** **US 6,603,330 B1**
(45) **Date of Patent:** **Aug. 5, 2003**

(54) **CONFIGURING DIGITAL FUNCTIONS IN A DIGITAL CONFIGURABLE MACRO ARCHITECTURE**

(75) Inventor: **Warren Snyder**, Snohomish, WA (US)

(73) Assignee: **Cypress Semiconductor Corporation**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/909,109**

(22) Filed: **Jul. 18, 2001**

Related U.S. Application Data

(60) Provisional application No. 60/243,708, filed on Oct. 26, 2000.

(51) Int. Cl.⁷ **H03K 19/173; H03K 19/00**

(52) U.S. Cl. **326/37; 326/101**

(58) Field of Search 326/37–41, 47, 326/101

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,202,687	A	4/1993	Distinti	341/158
5,426,378	A *	6/1995	Ong	326/38
5,703,871	A *	12/1997	Pope et al.	370/248
5,828,693	A *	10/1998	Mays et al.	375/136
5,880,598	A	3/1999	Duong	326/41
6,018,559	A *	1/2000	Azegami et al.	377/79
6,144,327	A	11/2000	Distinti et al.	341/126
6,304,101	B1	10/2001	Nishihara	326/41

OTHER PUBLICATIONS

CYPR-CD00170; “Digital Configurable Macro Architecture”; Jul. 18, 2001; 09/909,045; W. Snyder.

CYPR-CD00232; “Programmable System On A Chip”; Oct. 1, 2001; 10/033,027; W. Snyder.

* cited by examiner

Primary Examiner—Michael Tokar


Assistant Examiner—James H Cho

(74) *Attorney, Agent, or Firm*—Wagner, Murabito & Hao LLP

(57) **ABSTRACT**

A new digital configurable macro architecture is described. The digital configurable macro architecture is well suited for microcontroller or controller designs. In particular, the foundation of the digital configurable macro architecture is a programmable digital circuit block. The programmable digital circuit blocks can be configured to coupled in series or in parallel to handle more complex digital functions. More importantly, the configuration of the programmable digital circuit block is determined by its small number of configuration registers. This provides much flexibility. In particular, the configuration of the programmable digital circuit block is fast and easy since changes in configuration are accomplished by changing the contents of the configuration registers, whereas the contents are generally a small number of configuration data bits. Thus, the programmable digital circuit block is dynamically configurable from one predetermined digital function to another predetermined digital function for real-time processing.

28 Claims, 9 Drawing Sheets






FIGURE 1




FIGURE 2

TIMER CONFIGURATION




FIGURE 3

COUNTER CONFIGURATION




FIGURE 4




FIGURE 5

TX UART CONFIGURATION




FIGURE 6

RX UART CONFIGURATION




FIGURE 7

SPI MASTER CONFIGURATION




FIGURE 8

SPI SLAVE CONFIGURATION




FIGURE 9

**CONFIGURING DIGITAL FUNCTIONS IN A
DIGITAL CONFIGURABLE MACRO
ARCHITECTURE**

This application claims priority to the copending provisional patent application, Ser. No. 60/243,708, Attorney Docket Number CYPR-CD00167, entitled "Advanced Programmable Microcontroller Device," with filing date Oct. 26, 2000, and assigned to the assignee of the present application.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to programmable digital circuits. More particularly, the present invention relates to the field of programmable digital circuits which are dynamically configurable to any one of various digital functions by changing the contents of configuration registers.

2. Related Art

Microcontrollers or controllers have been utilized in various applications for many years. Primarily, microcontrollers are used in control-oriented applications that are interrupt-driven, sensing and controlling external events. Microcontrollers are frequently found in: appliances (e.g., microwave oven, refrigerator, television, VCR, stereo), computers and computer equipment (e.g., laser printers, modems, disk drives), automobiles (e.g., engine control, diagnostics, climate control), environmental control (e.g., greenhouse, factory, home), aerospace, and thousands of other uses.

The Field Programmable Gate Array (FPGA) has become very popular in recent years, even being utilized in several microcontroller applications. One reason for its popularity is the shortage in design cycle time that may be achieved by using programmable devices. Typically, FPGAs offer the highest logic capacity. FPGAs can be programmed to realize different digital functions. In particular, many FPGAs have programmable look-up tables to realize different digital functions. Typically, a FPGA contains from a few to tens of thousands of programmable logic blocks and an even greater number of flip-flops, each programmable logic block having a look-up table, multiplexors, and flip-flops. Most FPGAs do not provide 100% interconnect between programmable logic blocks.

However, FPGAs are highly inefficient with respect to chip area, increasing their cost. Typically, less than half of the logic resources in the FPGA are used to realize a digital function. Moreover, FPGAs need to have their look-up tables re-programmed in order to enable them to implement a new digital function, which is a time consuming task.

FPGAs are not ideally suited for microcontroller applications. Microcontroller applications are very cost-sensitive. A FPGA is not able to realize the number of digital functions that are demanded by today's microcontroller applications within these strict cost constraints.

SUMMARY OF THE INVENTION

A new digital configurable macro architecture is described. The digital configurable macro architecture is well suited for microcontroller or controller designs. In particular, the foundation of the digital configurable macro architecture is a programmable digital circuit block. In an embodiment, programmable digital circuit blocks are 8-bit circuit modules that can be programmed to perform any one of a variety of predetermined digital functions by changing

the contents of a few registers therein, unlike a FPGA which is a generic device that can be programmed to perform any arbitrary digital function. Specifically, the circuit components of the programmable digital circuit block are designed for reuse in several of the predetermined digital functions such that to minimize the size of the programmable digital circuit block. The programmable digital circuit blocks can be configured, for example, as timers, counters, serial communication ports, cyclic redundancy generators/checkers (CRC), or pseudo random sequence generators (PRS). The user selects the digital function that is needed and configures the programmable digital circuit block accordingly.

The programmable digital circuit blocks can be configured to coupled in series or in parallel to handle more complex digital functions. For example, a 24-bit timer can be designed by coupling three 8-bit programmable digital circuit blocks that have been individually configured as 8-bit timers. Additionally, a first programmable digital circuit block that is configured as a CRC generator can feed a second programmable digital circuit block that is configured as a serial output communication port.

More importantly, the configuration of the programmable digital circuit block is determined by its small number of configuration registers. This provides much flexibility. In particular, the configuration of the programmable digital circuit block is fast and easy since changes in configuration are accomplished by changing the contents of the configuration registers, whereas the contents are generally a small number of configuration data bits. Thus, the programmable digital circuit block is dynamically configurable from one predetermined digital function to another predetermined digital function for real-time processing.

These and other advantages of the present invention will no doubt become apparent to those of ordinary skill in the art after having read the following detailed description of the preferred embodiments which are illustrated in the drawing figures.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the present invention.

FIG. 1 illustrates a programmable digital circuit block in accordance with an embodiment of the present invention.

FIG. 2 illustrates a block diagram of an exemplary programmable digital device having a plurality of programmable digital circuit blocks in accordance with an embodiment of the present invention.

FIG. 3 illustrates a block diagram of a timer configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

FIG. 4 illustrates a block diagram of a counter configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

FIG. 5 illustrates a block diagram of a pulse width modulator (PWM) configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

FIG. 6 illustrates a block diagram of a UART transmitter configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

FIG. 7 illustrates a block diagram of a UART receiver configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

US 6,603,330 B1

3

FIG. 8 illustrates a block diagram of a SPI Master configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

FIG. 9 illustrates a block diagram of a SPI Slave configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

The drawings referred to in this description should not be understood as being drawn to scale except if specifically noted.

DETAILED DESCRIPTION OF THE INVENTION

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. While the invention will be described in conjunction with the preferred embodiments, it will be understood that they are not intended to limit the invention to these embodiments. On the contrary, the invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the invention as defined by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be recognized by one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present invention.

FIG. 1 illustrates a programmable digital circuit block **100** in accordance with an embodiment of the present invention. The programmable digital circuit block **100** is the foundation of a new digital configurable macro architecture of the present invention. The digital configurable macro architecture is well suited for microcontroller or controller designs.

The design of the programmable digital circuit block **100** in the digital configurable macro architecture was developed after examining and studying conventional microcontrollers to determine the types of digital functions that were implemented within various conventional microcontrollers. It was discovered that there were not very many different types of digital functions demanded in microcontroller applications. Furthermore, it was determined that these different types of digital functions had many circuit components in common. Moreover, it was determined that the digital functions were generally implemented as 8-bit or multiples of 8-bits because their length was generally based on the length of standard buses. This led to the development of the programmable digital circuit blocks **100**, the building block of the digital configurable macro architecture.

In an embodiment, the programmable digital circuit block **100** is an 8-bit circuit module that can be programmed to perform any one of a variety of predetermined digital functions (which are useful in microcontroller applications) by changing the contents of a few configuration registers **50** therein, unlike a FPGA which is a generic device that can be programmed to perform any arbitrary digital function. Specifically, the circuit components of the programmable digital circuit block **100** are designed for reuse in several of the predetermined digital functions such that to minimize the size of the programmable digital circuit block **100**. Hence, the programmable digital circuit block **100** is highly efficient in terms of die area. In an embodiment, the programmable digital circuit block **100** can be configured as a timer, a

4

counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), a dead zone delay, a UART (universal asynchronous receiver-transmitter) transmitter, a UART (universal asynchronous receiver-transmitter) receiver, a SPI (serial peripheral interface) Master, or a SPI (serial peripheral interface) Slave.

In another embodiment, the programmable digital circuit block **100** can be configured as a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), or a dead zone delay, whereas the digital communication functions (e.g., UART and SPI) are eliminated to further reduce the size of the programmable digital circuit block **100**. In particular, the user selects the digital function that is needed and configures the programmable digital circuit block **100** accordingly. It should be understood that the programmable digital circuit block **100** can be designed to implement other digital functions.

A design can have an array of programmable digital circuit blocks **100** which can be configured to coupled together in series or in parallel to handle more complex digital functions or to increase precision. For example, a 24-bit timer can be designed by coupling three 8-bit programmable digital circuit blocks **100** that have been individually configured as 8-bit timers. Similarly, the 8-bit timer can be extended to 16- or 32-bit digital functions by coupling multiple programmable digital circuit blocks **100** together. Additionally, a first programmable digital circuit block that is configured as a CRC generator can feed a second programmable digital circuit block that is configured as a serial output communication port, reducing device programming and increasing performance.

More importantly, the configuration of the programmable digital circuit block **100** is determined by its configuration registers **50**. The programmable digital circuit block **100** generally has one or more configuration registers **50**. This provides much flexibility. In particular, the configuration of the programmable digital circuit block **100** is fast and easy to configure and re-configure since changes in configuration are accomplished by changing the contents of the configuration registers **50**, whereas the contents are generally a small number of configuration data bits. Thus, the programmable digital circuit block **100** is dynamically configurable from one predetermined digital function to another predetermined digital function for real-time processing. In contrast, FPGAs need to have their look-up tables re-programmed in order to have them implement a new digital function, a time-consuming task that is not done in real-time processing.

Referring to FIG. 1, in an embodiment the programmable digital circuit block **100** includes one or more configuration registers **50**, one or more data registers **40**, a plurality of selectable logic circuits **30**, one or more configurable inputs **20**, one or more configurable outputs **10**, one or more cascade outputs **60**, one or more cascade inputs **70**, a clock input **80**, and a system input **90**. It should be understood that the programmable digital circuit block **100** can have other designs including lengths other than 8-bits.

The configuration registers **50** are programmed via the system bus **90**. Any device, such as a microprocessor using data stored in a RAM or flash memory, can program (or write to) the configuration registers. The configuration registers **50** receive and store a plurality of configuration data corresponding to any one of the plurality of predetermined digital function described above. The programmed configu-

US 6,603,330 B1

5

ration registers **50** configure the programmable digital circuit block **100** to perform any one of the predetermined digital functions based on the configuration data. Moreover, the configuration registers **50** can be dynamically programmed with the configuration data for real-time processing. In addition, the configuration data includes (1) bits for indicating one of the predetermined digital functions and configuring the selectable logic circuits **30**, (2) bits for configuring and selecting the configurable inputs **20** and the configurable outputs **10** and the clock input **80**, (3) bits for indicating the mode of the predetermined digital function (e.g., parity, no parity, etc.), (4) bits for indicating the length of the predetermined digital function if several programmable digital circuit block **100** are coupled together (e.g., 8-bit, 16-bit, 24-bit, etc.), and (5) bits for indicating and configuring the interface between adjacent programmable digital circuit blocks **100** that are coupled together (e.g., configuring and selecting the cascade inputs **70** and the cascade outputs **60** for serial or parallel interfacing).

In general, the number of bits in the configuration data is sufficiently small to enable the configuration registers **50** to be programmed on-the-fly so that the programmable digital circuit block **100** can be dynamically configured and interfaced. Thus, the programmable digital circuit blocks **100** can be configured as a timer for a first length of time, re-configured as a counter for a second length of time, re-configured as a PWM for a third length of time, and so on, for real-time processing. For example, it is possible for a single register write to configure the programmable digital circuit block **100** from a timer to a PWM or to a counter or to a CRC generator or etc.

The connections **50A–50F** between the configuration registers **50** and other components of the programmable digital circuit block **100** enable the configuration registers **50** to properly configure the programmable digital circuit block **100** to any one of the predetermined digital functions and to properly interface the programmable digital circuit block **100** with other programmable digital circuit blocks in series or in parallel.

Continuing with FIG. 1, the selectable logic circuits **30** are tailored such that they have a minimum set of circuit resources that can be programmed by the configuration registers **50** to implement any one of a variety of predetermined digital functions, unlike the FPGA where a substantial amount of circuit resources may remain unused. In particular, the design and structure of the selectable logic circuits **30** are dependent on the predetermined digital functions such that to minimize the size of the programmable digital circuit block **100**. The fixed number of digital functions for the programmable digital circuit block **100** substantially influences the design of the programmable digital circuit block **100**, providing cost savings and improving performance. The configuration registers **50** configure and select any of the selectable logic circuits **30** to perform one of the predetermined digital functions based on the configuration data. More importantly, the selectable logic circuits **30** are reused in several of the predetermined digital functions as will be illustrated below, ensuring the size efficiency of the programmable digital circuit block **100**. In an embodiment, the selectable logic circuits **30** include a plurality of logic gates.

Moreover, the selectable logic circuits **30** realize any one of the variety of predetermined digital functions by using the data registers **40** to receive data, load data, capture data, etc. Thus, the data registers **40** are also reused in several of the predetermined digital functions as will be illustrated below.

Again referencing FIG. 1, the cascade outputs **60** and the cascade inputs **70** are selected and configured according to

6

the configuration data. The cascade outputs **60** allow the programmable digital circuit block **100** to output signals for directly interfacing with adjacent or neighboring programmable digital circuit blocks. The cascade inputs **70** allow the adjacent or neighboring programmable digital circuit blocks to send signals that directly interface and are received by the programmable digital circuit block **100**. Specifically, the cascade outputs **60** and the cascade inputs **70** enable multiple programmable digital circuit blocks to seamlessly interface to handle more complex digital functions or to increase precision as described above (e.g., 32-bit timer, CRC generator and SPI Master, 24-bit counter, etc.).

FIG. 2 illustrates a block diagram of an exemplary programmable digital device **200** having a plurality of programmable digital circuit blocks **210A–210H** in accordance with an embodiment of the present invention. The plurality of programmable digital circuit blocks **210A–210H** includes a first group and a second group. The first group includes the programmable digital circuit blocks **210A–210B** and **210E–210F**. Moreover, each programmable digital circuit block of the first group can be configured as a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), or a dead zone delay. The second group includes the programmable digital circuit blocks **210C–210D** and **210G–210H**. Moreover, each programmable digital circuit block of the second group can be configured as a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), a dead zone delay, a UART (universal asynchronous receiver-transmitter) transmitter, a UART (universal asynchronous receiver-transmitter) receiver, a SPI (serial peripheral interface) Master, or a SPI (serial peripheral interface) Slave.

As illustrated in FIG. 2, adjacent or neighboring programmable digital circuit blocks are interfaced via cascade lines **205** (input or output) as described above. The cascade lines **205** enable the programmable digital circuit blocks **210A–210H** to seamlessly interface to handle more complex digital functions or to increase precision. For example, a 32-bit counter can be designed by coupling four 8-bit programmable digital circuit blocks that have been individually configured as 8-bit counters. Similarly, the 8-bit counter can be extended to 16- or 24-bit digital functions by coupling multiple programmable digital circuit blocks together. Additionally, a first programmable digital circuit block that is configured as a CRC generator can feed a second programmable digital circuit block that is configured as a serial output communication port, reducing device programming and increasing performance.

Moreover, the exemplary programmable digital device **200** includes a signal bus for digitized analog signals, a clock bus, a system bus for programming the programmable digital circuit blocks **210A–210H**, and a plurality of global data buses for transmitting data to/from the programmable digital circuit blocks **210A–210H**.

FIG. 3 illustrates a block diagram of a timer configuration of a programmable digital circuit block in accordance with an embodiment of the present invention. FIG. 4 illustrates a block diagram of a counter configuration of a programmable digital circuit block in accordance with an embodiment of the present invention. FIG. 5 illustrates a block diagram of a pulse width modulator (PWM) configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

As illustrated in FIGS. 3–5, the selectable logic circuits **320** and **340** are reused for the timer, counter, and PWM

US 6,603,330 B1

7

configurations. Moreover, the first data register **310**, the second data register **330**, and the third data register **350** of the programmable digital circuit block are reused for the timer, counter, and PWM configurations. In essence, the configuration data loaded onto the configuration registers determines how the data registers **310**, **330**, and **350** are to be used, what operation is to be performed on the data by the selectable logic circuits **320** and **340**, where the input data is selected from (e.g., system bus (SB), signal bus, global bus, etc.), where the output data is transmitted, what clock signal is to be used, what are the cascade inputs (e.g., DIN, CI, etc.) from other programmable digital circuit blocks, what are the cascade outputs (e.g., DOUT, CO, etc.) to other programmable digital circuit blocks, when to generate an interrupt (INT), and what is the data flow within the programmable digital circuit block so that the programmable digital circuit block can properly perform any one of the predetermined digital functions.

FIG. 6 illustrates a block diagram of a UART transmitter configuration of a programmable digital circuit block in accordance with an embodiment of the present invention. FIG. 7 illustrates a block diagram of a UART receiver configuration of a programmable digital circuit block in accordance with an embodiment of the present invention. FIG. 8 illustrates a block diagram of a SPI Master configuration of a programmable digital circuit block in accordance with an embodiment of the present invention. FIG. 9 illustrates a block diagram of a SPI Slave configuration of a programmable digital circuit block in accordance with an embodiment of the present invention.

As illustrated in FIGS. 6–9, the selectable logic circuits **410** and **420** are reused for the UART transmitter, the UART receiver, the SPI Master, and the SPI Slave configurations. Moreover, the first data register **310**, the second data register **330**, and the third data register **350** of the programmable digital circuit block are reused in several of the UART transmitter, the UART receiver, the SPI Master, and the SPI Slave configurations. However, the selectable logic circuit **430** is used in the UART transmitter configuration of FIG. 6 since the UART protocol requires that particular protocol bits (e.g., start bits, stop bits, etc.) to be generated by the UART transmitter.

FIGS. 3–9 illustrate that the programmable digital circuit block can be configured fast and easily. Furthermore, FIGS. 3–9 illustrate that the programmable digital circuit block is highly efficient in terms of die area.

The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the Claims appended hereto and their equivalents.

What is claimed is:

1. A programmable digital circuit block comprising:

- a system input for inputting a plurality of configuration data corresponding to any one of a plurality of predetermined digital functions;
- a configuration register coupled to said system input for receiving and storing said configuration data and for

8

configuring said programmable digital circuit block to perform any one of said plurality of predetermined digital functions based on said configuration data, wherein said configuration register is dynamically programmable with said configuration data;

- a plurality of selectable logic circuits which are dependent on said plurality of predetermined digital functions such that to minimize size of said programmable digital circuit block, wherein said configuration register configures and selects any of said selectable logic circuits to perform one of said plurality of predetermined digital functions based on said configuration data; and
- a data register coupled to said selectable logic circuits for storing data to facilitate performing any one of said plurality of predetermined digital functions.

2. The programmable digital circuit block as recited in claim 1 further comprising:

- one or more inputs for receiving input data associated with any one of said plurality of predetermined digital functions;
- one or more outputs for outputting output data associated with any one of said plurality of predetermined digital functions; and
- at least one clock input for receiving a clock signal.

3. The programmable digital circuit block as recited in claim 2 wherein said configuration register configures and selects said one or more inputs, said one or more outputs, and said clock input based on said configuration data.

4. The programmable digital circuit block as recited in claim 2 further comprising:

- one or more cascade inputs for receiving data from one or more adjacent programmable digital circuit blocks; and
- one or more cascade outputs for outputting data to said one or more adjacent programmable digital circuit blocks.

5. The programmable digital circuit block as recited in claim 4 wherein said configuration register configures and selects said one or more cascade inputs and said one or more cascade outputs based on said configuration data.

6. The programmable digital circuit block as recited in claim 1 wherein said predetermined digital functions include a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), a dead zone delay, a UART transmitter, a UART receiver, a SPI Master, and a SPI Slave.

7. The programmable digital circuit block as recited in claim 1 wherein said predetermined digital functions include a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), and a dead zone delay.

8. The programmable digital circuit block as recited in claim 1 wherein said predetermined digital functions are 8-bit predetermined digital functions.

9. A programmable digital device comprising:

- an array of programmable digital circuit blocks, each programmable digital circuit block comprising:
 - a system input for inputting a plurality of configuration data corresponding to any one of a plurality of predetermined digital functions;
 - a configuration register coupled to said system input for receiving and storing said configuration data and for configuring said programmable digital circuit block to perform any one of said plurality of predetermined digital functions based on said configuration data, wherein said configuration register is dynamically programmable with said configuration data;

US 6,603,330 B1

9

a plurality of selectable logic circuits which are dependent on said plurality of predetermined digital functions such that to minimize size of said programmable digital circuit block, wherein said configuration register configures and selects any of said selectable logic circuits to perform one of said plurality of predetermined digital functions based on said configuration data; and
 a data register coupled to said selectable logic circuits for storing data to facilitate performing any one of said plurality of predetermined digital functions.

10. The programmable digital device as recited in claim 9 wherein each programmable digital circuit block further comprises:

one or more inputs for receiving input data associated with any one of said plurality of predetermined digital functions;

one or more outputs for outputting output data associated with any one of said plurality of predetermined digital functions; and

at least one clock input for receiving a clock signal.

11. The programmable digital device as recited in claim 10 wherein said configuration register configures and selects said one or more inputs, said one or more outputs, and said clock input based on said configuration data.

12. The programmable digital device as recited in claim 10 wherein each programmable digital circuit block further comprises:

one or more cascade inputs for receiving data from one or more adjacent programmable digital circuit blocks; and
 one or more cascade outputs for outputting data to said one or more adjacent programmable digital circuit blocks.

13. The programmable digital device as recited in claim 12 wherein said configuration register configures and selects said one or more cascade inputs and said one or more cascade outputs based on said configuration data.

14. The programmable digital device as recited in claim 9 wherein said predetermined digital functions include a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), a dead zone delay, a UART transmitter, a UART receiver, a SPI Master, and a SPI Slave.

15. The programmable digital device as recited in claim 9 wherein said predetermined digital functions include a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), and a dead zone delay.

16. The programmable digital device as recited in claim 9 wherein said predetermined digital functions are 8-bit predetermined digital functions.

17. A controller apparatus comprising:

a programmable digital circuit block comprising:

a system input for inputting a plurality of configuration data corresponding to any one of a plurality of predetermined digital functions;

a configuration register coupled to said system input for receiving and storing said configuration data and for configuring said programmable digital circuit block to perform any one of said plurality of predetermined digital functions based on said configuration data, wherein said configuration register is dynamically programmable with said configuration data;

10

a plurality of selectable logic circuits which are dependent on said plurality of predetermined digital functions such that to minimize size of said programmable digital circuit block, wherein said configuration register configures and selects any of said selectable logic circuits to perform one of said plurality of predetermined digital functions based on said configuration data; and

a data register coupled to said selectable logic circuits for storing data to facilitate performing any one of said plurality of predetermined digital functions.

18. The controller apparatus as recited in claim 17 wherein said programmable digital circuit block further comprises:

one or more inputs for receiving input data associated with any one of said plurality of predetermined digital functions;

one or more outputs for outputting output data associated with any one of said plurality of predetermined digital functions; and

at least one clock input for receiving a clock signal.

19. The controller apparatus as recited in claim 18 wherein said configuration register configures and selects said one or more inputs, said one or more outputs, and said clock input based on said configuration data.

20. The controller apparatus as recited in claim 18 wherein said programmable digital circuit block further comprises:

one or more cascade inputs for receiving data from one or more adjacent programmable digital circuit blocks; and
 one or more cascade outputs for outputting data to said one or more adjacent programmable digital circuit blocks.

21. The controller apparatus as recited in claim 20 wherein said configuration register configures and selects said one or more cascade inputs and said one or more cascade outputs based on said configuration data.

22. The controller apparatus as recited in claim 17 wherein said predetermined digital functions include a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), a dead zone delay, a UART transmitter, a UART receiver, a SPI Master, and a SPI Slave.

23. The controller apparatus as recited in claim 17 wherein said predetermined digital functions include a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), and a dead zone delay.

24. The controller apparatus as recited in claim 17 wherein said predetermined digital functions are 8-bit predetermined digital functions.

25. A method of programming a programmable digital circuit block, comprising the steps of:

a) loading a plurality of configuration data corresponding to any one of a plurality of predetermined digital functions into a configuration register of said programmable digital circuit block; and

b) configuring said programmable digital circuit block to perform any one of said plurality of predetermined digital functions based on said configuration data, wherein said steps a) and b) are dynamically performed, and wherein said programmable digital circuit block includes a data register for storing data to facilitate performing any one of said plurality of predetermined digital functions.

US 6,603,330 B1

11

26. The method as recited in claim 25 wherein said predetermined digital functions include a timer, a counter, a pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), a dead zone delay, a UART transmitter, a 5 UART receiver, a SPI Master, and a SPI Slave.

27. The method as recited in claim 25 wherein said predetermined digital functions include a timer, a counter, a

12

pulse width modulator (PWM), a cyclic redundancy generator/checker (CRC), a pseudo random sequence generator (PRS), and a dead zone delay.

28. The method as recited in claim 25 wherein said predetermined digital functions are 8-bit predetermined digital functions.

* * * * *